



## LV-6715 – Mini ITX Motherboard with Intel®Alder Lake H Core i7-12800HE Processor Onboard

This Intel® Alder Lake Mini-ITX Motherboard features the Core i7-12800HE processor. With multiple M.2 slots for Wifi, Bluetooth, storage and expansion, this board is ideal for Automation, IoT, Surveillance, and other Industrial uses. Although this board has Intel's® IRIS® XE Graphics onboard with  $2 \times HDMI$ ,  $2 \times DP$ , and  $1 \times HDMI/DVI$  or onboard LVDS, it also allows for a PCle x16 slot for advanced graphics cards. There are two options for power - either standard 24-pin ATX or 4-pin DC 9~35V. Multiple USB, COM and  $2 \times LAN$  add to the many features of this unique Mini-ITX Motherboard.

## **SPECIFICATIONS**

Video

Internal I/O

**Power Requirement** 

CPU Intel® Core i7-12800HE

 $2 \times DDR5$  SO-DIMM 4800 MHz up to 64 GB, Support Non-ECC unbuffered **Memory Type** 

memory

Memory Slots 2

**Maximum Memory Supported** 64GB

Audio Realtek ALC888S HD Audio

Integrated Graphics Intel® Iris® Xe Graphics

**Watchdog Timer** Generates a system reset with internal timer for 1 min/s ~ 255min/s

**Serial ATA (SATA)** 2 x SATA3 (mSATA and SATA3-2 can't be use at the same time)

 $1 \times \text{LVDS}$  (mSATA and SATA2 can't be used at the same time),  $1 \times \text{DVI/HDMI}$ ,  $2 \times \text{DVI/HDMI}$ ,  $2 \times \text{DVI/HDMI}$ ,  $2 \times \text{DVI/HDMI}$ 

HDMI, 2 x Display Port

TPM Yes; fTPM

1 x Intel® I219-LM Gigabit PHY LAN (supports Intel® AMT 16.0), 2x Intel® I226-LAN Ports

LM Gigabit LAN (up to 2.5 GbE)

1 x MiniPCle (supports mSATA when SATA3-2 is not used), 2 x M.2 2280 M-Key

**Extended Interface** (supports PCle Gen4 for NVMe), 1 x M.2 2230 E-Key (for Wi-Fi and Bluetooth), 1 x

PCle x16 Slot (supports Gen4 X8)

2 x SATA3, 4 x RS232, 2 x USB2.0, 1 x GPIO, 1 x SMBus, 1 x Audio, 1 x LAN, 1 x

LVDS, 1 x LCD inverter, 1 x DVI/HDMI

4 x USB3.2 Gen2, 2 x USB2.0, 2 x LAN, 2 x RS232/422/485, 1 x Audio, 2 x

Rear I/O HDMI, 2 x DisplayPort

Standard 24-pin ATX power supply or 4-pin 9~35V

**Dimensions** 170 mm x 170 mm

**Operating Temperature**  $0 \sim 60^{\circ} \text{ C} (32 \sim 140^{\circ} \text{ F})$ 

**Storage Temperature**  $-20 \sim 80 \,^{\circ}\text{C} \, (-4 \sim 176 \,^{\circ}\text{F})$ 

**Relative Humidity** 10%~90%, non-condensing

**OS Software Supported** Windows 10 Professional 64-bit, Windows 11

**Global P/N / SKU** 2809153

## **Ordering Options**

LV-67157 – With Core i7-1270PE and Cooler Fan Add ADP-3355 for VGA through the Display Port Add ADP-3460 for 2nd LVDS through the Display Port

## Some of our successful brand partners





