

## LE-37T – 3.5" Miniboard with Intel® Atom Processor X Series (Amston Lake)

The LE-37T 3.5 inch Miniboard platform is designed for Intel® AtomTM Processors in the FCBGA1264 package support DDR5 memory (One DDR5 SO-DIMM up to 4800 MHz 32GB).

The platform is based on Intel® UHD Graphics, this GPU offers 32 execution units (EUs) clocked at up to 800Mhz(depending on the CPU model). Displays can be connected via one LVDS, one HDMI, one DP++, one Type-C (DP Alt Mode) port for displays can be controlled simultaneously. LE-37T offers lots of features including high-speed data transfer interfaces such as  $2 \times USB3.2 \, Gen2$  and  $1 \times SATA3$ , equipped with triple Gigabit Ethernet, and comes with  $4 \times RS232$  and  $2 \times RS232/422/485$ ,  $2 \times USB2.0$ , Intel® High Definition Audio,  $1 \times M.2$  Key E 2230,  $1 \times M.2$  Key M 2280 support Gen3 PCle x4 for NVMe.

## **SPECIFICATIONS**

CPU Intel® Atom Processor X Series (Amston Lake)

Memory Type 262-pin DDR5 4800MHz SO-DIMM

Memory Slots

Maximum Memory Supported 32GB

**Watchdog Timer** Generates a system reset with internal timer for 1 min/s ~ 255 min/s

**GPIO Interface** Onboard programmable 8-bit Digital I/O interface

Integrated Graphics Intel® UHD Graphics

Video 1 x DisplayPort++, 1 x HDMI, 1 x Type-C(DP Alt. Mode), 1 x LVDS

**LAN Ports** 2 x Intel® I226 Gigabit LAN (Up to 2.5GbE)

Serial ATA (SATA) 1 x Serial ATA3 (for OEM)

**Extended Interface** 1 x M.2 Key M 2280 support Gen3 PCle x4 for NVMe, 1 x M.2 Key E 2230 for Wi-

Fi and Bluetooth

1 x SATA3(for OEM), 2 x RS232/422/485, 4 x RS232, 2 x USB2.0, 1 x LVDS, 1 x Internal I/O

LCD inverter connector, 1 x GPIO, 1 x SMBus, 1 x Audio (MIC-in, Line-out), 1 x

Speaker Out with Amp

1 x DisplayPort++, 1 x HDMI, 2 x USB 3.2 Gen2, 2 x LAN, 1 x Type-C (DP Alt. Rear I/O

Mode)

**Audio** Realtek ALC888S HD Audio with 3 Watt amplifier for 4 ohm speaker

**Power Requirement** DC input 9~35V

**Dimensions** 5.75" x 3.98" (146mm x 101mm)

**Operating Temperature** -40°C ~ 85°C (-40°F ~ 185°F)

**Storage Temperature** -40°C ~ 85°C (-40°F ~ 185°F)

**Relative Humidity** 10% to 90% (non condensing)

**OS Software Supported** Windows 10 Professional 64-bit, Windows 11

Global P/N / SKU 3309001

## **Ordering Options**

3309001A - LE-37TX4 with AtomTM x7433RE + Heat Spreader 3309001B - OEM LE-37TX8 with AtomTM x7835RE + Cooler Fan 3309001C - OEM LE-37TX2 with AtomTM x7213RE + Heat Spreader 3309001D - OEM LE-37TX1 with AtomTM x7211RE + Heat Spreader Note: SATA port for OEM

## Some of our successful brand partners

