



## **IMB542 – ATX Motherboard with 14th/13th/12th Gen Intel® Core™ i9/i7/i5/i3 Support**

The IMB542 is an ATX Motherboard that supports 14th/13th/12th Gen processors. The motherboard supports up to 192GB of non-ECC DDR5 RAM and up to 3 displays using VGA, DVI, and HDMI interfaces.

### **SPECIFICATIONS**

<b>CPU</b>	14th/13th/12th Gen Intel® Core™ i9/i7/i5/i3, Pentium® or Celeron® processor (up to 125W)
<b>Chipset</b>	Intel® Q670
<b>Memory Type</b>	288-pin DDR5-4400 non-ECC Long-DIMM
<b>Memory Slots</b>	4
<b>Maximum Memory Supported</b>	192GB
<b>Integrated Graphics</b>	Intel® UHD Graphics
<b>Audio</b>	HD Codec Audio
<b>Video</b>	1 x VGA, 1 x DVI-D, 1 x HDMI 2.0
<b>LAN Ports</b>	1 x 10/100/1000 Mbps (Intel® I210-AT), 1 x 10/100/1000 Mbps (Intel® I219-V)
<b>Serial ATA (SATA)</b>	4 x SATA-600 with RAID 0/1/5/10

<b>TPM</b>	Not included by default; supports Intel® PTT as default
<b>Watchdog Timer</b>	255 levels, 1 to 255 sec
<b>Extended Interface</b>	1 x M.2 Key M 2280 PCIe x4, 1 x M.2 Key E 2230 (PCIe x1 + USB 2.0), 2 x PCIe x16 (Gen4 x16 + Gen3 x4), 3 x PCIe Gen4 x4, 2 x PCI
<b>Rear I/O</b>	1 x RS-232, 1 x PS/2, 6 x USB 3.2 Gen1x1, 1 x DVI, 1 x VGA, 1 x HDMI, 2 x LAN, 1 x MIC/Line-In/Line-Out
<b>Internal I/O</b>	3 x RS-232, 1 x RS-232/422/485, 1 x RS-232/485, 2 x USB 3.2 Gen1x1, 4 x USB 2.0, 1 x USB 2.0 (internal 180D Type-A)
<b>Power Requirement</b>	24 + 8-pin ATX connector
<b>Operating Temperature</b>	0°C ~ 60°C (32°F ~ 140°F)
<b>Relative Humidity</b>	10 ~ 95% (non-condensing)
<b>OS Software Supported</b>	Windows 11 64-bit
<b>Global P/N / SKU</b>	2809205

## Ordering Options

IMB542 (SKU# 2809205): ATX motherboard with LGA1700 socket 14th/13th/12th Gen Intel® Core™ i9/i7/i5/i3, Pentium® or Celeron® processor, Intel® Q670, USB 3.2 Gen 1x1, SATA 3.0, GbE LAN, VGA, DVI-D, and HDMI

Some of our successful brand  
partners